

G80 Eye Self-Locking Hook with Grip (TCSH077)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.



Size	W.L.L (t)	B.L (t)	Dimension (mm)					N.W. (kg/pc)
			A	H	E	L	Φ	
7/8-8	2	8	25	21.5	34	163	40	0.75
10-8	3.15	12.6	32	26.2	42	201.5	50	1.2
13-8	5.3	21.2	40	31	50	243.5	60	2
16-8	8	32	50	39.5	60	298	70	4.1



G80 Clevis Self-Locking Hook with Grip (TCSH078)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.



Size	W.L.L (t)	B.L (t)	Dimension (mm)					N.W. (kg/pc)
			A	H	E	L	Φ	
7/8-8	2	8	9.5	21.5	36	149	40	0.6
10-8	3.15	12.6	12	26.2	44	18	50	1.1
13-8	5.3	21.2	15	31	54	229	60	2
16-8	8	32	18	39.5	63	270	70	4.2



G80 Special Webbing Connecting Link (TCSH079)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.



Size	W.L.L (t)	B.L (t)	Dimension (mm)					N.W. (kg/pc)
			A	M	H	K	L	
19-8	12.5	50	37	26.2	20	186.5	246	3.4
22-8	15	60	48	28.2	25	205.5	273	4.55
25-8	20	80	51.5	33	30	231	306	6.1



G80 European Type Eye Self-Locking Hook (TCSH081)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.



Size	W.L.L (t)	B.L (t)	Dimension (mm)						N.W. (kg/pc)
			Φ1	R	D	Φ2	H	E	
6-8	1.12	4.48	22	110.5	10	34	19.5	28	0.5
7/8-8	2	8	25	136	12	46	24	34	0.8
10-8	3.15	12.6	32	171	15	56	28.5	44	1.55
13-8	5.3	21.2	40.5	208.5	19.5	69	40	52	3.2
16-8	8	32	56	257.5	22	86	50.5	60	5.74
20-8	12.5	50	64.5	275	27	100	55	81	8.5
22-8	15	60	70	320	30	98	67	82	13
26-8	21.2	84.8	80	363	334	110	75	110	18
32-8	31.5	126	105	472	45	166	97	168	44.5



G80 European Type Clevis Self-Locking Hook (TCSH082)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.



Size	W.L.L (t)	B.L (t)	Dimension (mm)					N.W. (kg/pc)
			E	B	H	Φ	R	
6-8	1.12	4.48	29	8.5	19.5	34	95.5	0.5
7/8-8	2	8	34	9.5	24	46	121	0.8
10-8	3.15	12.6	44	12	28.5	56	146	1.5
13-8	5.3	21.2	52	15	40	69	182	2.8
16-8	8	32	60	18	50.5	86	218	5.6
20-8	12.5	50	83	25	55	100	240	7.5
22-8	15	60	88	25.5	67	98	276.5	11.5
26-8	21.2	84.8	95.5	30	75	110	310.5	18.5



G80 European Swivel Self-Locking Hook (TCSH083)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.



Size	W.L.L (t)	B.L (t)	Dimension (mm)						N.W. (kg/pc)
			B	C	D	L	T	E	
6-8	1.12	4.48	32.5	22	11.25	170	34	29	0.71
7/8-8	2	8	35.5	26	12.5	210	46	34	1.1
10-8	3.15	12.6	42	34	15	247	56	44	2.0
13-8	5.3	21.2	50	38.5	16	302	69	52	4.0
16-8	8	32	61	55	21.5	383	86	60	7.3
20-8	12.5	50	72	61	26	418	100	83	11.6
22-8	15	60	95	95	33	527	98	88	16.0
26-8	21.2	84.8	122	115	42	610	110	95.5	21.5
32-8	31.5	126	140	146	52	777	166	150	79



G80 Eye Shortening Grab Hook (TCSH085)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.



Size	W.L.L (t)	B.L (t)	Dimension (mm)					N.W. (kg/pc)
			E	Φ	H	R	L	
6-8	1.12	4.48	8	13.5	16	51	75.2	0.14
7/8-8	2	8	10.8	17	18.5	60.5	88.5	0.246
10-8	3.15	12.6	13	20	29	79.5	121.5	0.65
13-8	5.3	21.2	16.5	26	42.8	99.7	158	1.39
16-8	8	32	19.2	30	45.7	104	169	2.2
20-8	12.5	50	24	37	56	140	219	4.6
22-8	15	60	28	44	68	165	259	8.2
26-8	21.2	84.8	30	41	77	188.5	298	9.8
32-8	31.5	126	38	57	95	228.5	361	19.34



G80 Clevis Shortening Grab Hook (TCSH086)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.



Size	W.L.L (t)	B.L (t)	Dimension (mm)				N.W. (kg/pc)
			E	A	H	L	
6-8	1.12	4.48	8	8	16	75	0.25
7/8-8	2	8	10.8	9.5	21.6	90	0.32
10-8	3.15	12.6	13.5	12.5	30	126	0.73
13-8	5.3	21.2	16.5	15	42.5	163.5	1.6
16-8	8	32	19.2	19.5	45.5	183.5	2.8
20-8	12.5	50	24	24	56	219	5
22-8	15	60	27	27	68.5	254	6.3